



































rolldolly® BASIC

- dimensions rolldolly® BASIC up to 300 kg load
- 610 x 410 x 190 mm / interior: 602 x 402 mm
- transportroller for Euronorm boxes 600 x 400 mm
- plastic base made of recycling material
- with four swivel castors ø 100 mm wheel center: polypropylene tread: thermoplastic rubber
- ideal securing of the plastic boxes through double safety edge
- dimensions rolldolly® XL BASIC up to 300 kg load **capacity:** 612 x 814 x 195 mm / interior: 602 x 804
- plastic base made of recycling material
- with two swivel and two fixed castors ø 100 mm wheel center: polypropylene tread: thermoplastic rubber
- ideal securing of the plastic boxes through double safety edge

rolldolly® BASIC	F92702RC90050L029
rolldolly® XL BASIC	E50000RC29005OL025

base BASIC

- base as transportroller up to 500 kg load capacity: 724 x 815 x 192 mm
- plastic base made of recycling material
- with two swivel and two fixed castors ø 108 mm wheel center: polypropylene tread: polypropylene
- base with foldable push handle up to 500 kg **load capacity:** 724 x 815 x 192 mm / interior: 660 x
- plastic base made of recycling material
- with two swivel and two fixed castors ø 108 mm wheel center: polypropylene tread: polypropylene

plastic base as transportroller	E10A00RC49005OL-001
plastic base with push handle	KB1A9005815CB00101R

gummitex® BASIC

- one hook / one loop 50 x 560 mm
- **two hooks** 50 x 520 mm
- high-quality mixed fabric made of PE fibres and elastic
- high working safety through UV resistance and longlasting mixed fabric
- max. recommended span length: 750 mm
- colour: dark grey, hooks: galvanized blue

gummitex® two hooks	E150001BL
gummitex® one hook / one loop	E150002BL



ESB Engineering - System - Bau GmbH

HEADQUARTERS Gewerbegebiet Lindental Lütke Haar 13 59602 Rüthen

FACTORY AND WAREHOUSE Gewerbegebiet Hankerfeld Hankerfeld 8 59602 Rüthen

+49 2952 - 970958-0 +49 2952 - 970958-29 info@esb-systembau.eu www.esb-systembau.eu

PARCEL SHIPPING

POSSIBLE

Due to the low

rolltainer® BASIC

can be delivered in a package.

self-weight a







rolltainer® BASIC

- dimensions 2-sided up to 500 kg load capacity: 724 x 815 x 1530 mm / interior: 664 x 815 x 1340 mm
- **dimensions 3-sided up to 500 kg load capacity:** 724 x 827 x 1530 mm / interior: 664 x 803 x 1340 mm
- dimensions 4-sided with a single-section door up to 500 kg load capacity: 724 x 845 x 1530 mm / interior: 664 x 803 x 1340 mm
- dimensions 4-sided with a two-section door up to 500 kg load capacity: 724 x 845 x 1530 mm / interior: 664 x 801 x 1340 mm
- plastic base made of recycling material
- with two swivel and two fixed castors ø 108 mm wheel center: polypropylene tread: polypropylene
- side panel, back wall and door made of Ø 20 x 1.5 mm all around tube frame, flat bar 12 x 3.0 mm
- surface: galvanized blue

2-sided	KB2A90051350CS0C801R
3-sided	KB3A90051350CS0C801R
4-sided with single-section door	KB4A90051350CS0C901R
4-sided with two-section door	KB4A90051350CS0C801R

- ideal for Euronorm boxes (also 4-sided)
- low self-weight
- light version
- parcel delivery possible



shelf

- **2- / 3- / 4-sided** 710 x 778 mm
- made of recycling material
- strengthend with 3 flat bars
- load capacity: 150 kg


shelf loose version E70A23RCF39005

rolltainer® ADB BASIC

- dimensions 3-sided up to 500 kg load capacity: 724 x 815 x 1800 mm / interior: 660 x 775 x 1610 mm
- **dimensions 4-sided up to 500 kg load capacity:** 724 x 815 x 1800 mm / interior: 660 x 750 x 1610 mm
- dimensions 5-sided anti-theft container up to 500 kg load capacity: 724 x 815 x 1810 mm / interior: 660 x 750 x 1585 mm
- large storage space for your products
- flexible arrangement of the intermediate shelves possible every 50 mm
- plastic base made of recycling material
- with two swivel and two fixed castors ø 108 mm wheel center: polypropylene tread: polypropylene
- side panel, back wall, door and roof made of ø 22 mm round tube with infill 50 x 50 x 4 mm
- surface: galvanized blue

3-sided	KAD3A90051600COZ101RC
4-sided	KAD4A90051600C0Z101RC
5-sided	KAD5A90051600COZ101RC
5-sided with fixed shelf	KAD5A90051600C1Z101RC

- stable version through ø 22 mm round tube lockable suitable for theft protection
- through the 50 x 50 mm mesh the shelves are variably insertable



shelf

- **2- / 3- / 4-sided** 700 x 705 mm
- suitable for rolltainer® and anti-theft
- wire shelf strengthend with flat bars
- without anti-slip edge
- variable attachable
- surface: galvanized blue
- load capacity: 150 kg

shelf loose version ZBD725ADLC000